

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

# FIELD NOTES

OF  
THE DEPENDENT RESURVEY OF  
A PORTION OF  
THE UINTAH INDIAN RESERVATION BOUNDARY  
FROM MILE POST 36 1/2 TO MILE POST 38 1/2,  
A PORTION OF THE SOUTH BOUNDARY,  
AND A PORTION OF THE SUBDIVISION LINES,  
AND THE SURVEY OF THE SUBDIVISION OF SECTION 26,  
IN  
TOWNSHIP 2 NORTH, RANGE 1 EAST  
OF THE UINTAH SPECIAL MERIDIAN, UTAH  
IN THE STATE OF UTAH

EXECUTED BY

*Jerry L. Thomas*  
*Cadastral Surveyor*

Under special instructions dated *April 18, 1994*, approved *April 18, 1994*, which provided for the surveys included under Group Number *815*, and assignment instructions dated *April 19, 1994*

Survey commenced *May 4, 1994*

Survey completed *June 8, 1994*

## INDEX DIAGRAM

Township 2 North, Range 1 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	14 27	12 26	25
		15	14	11	
31	32	33	13 34	10 35	9 36
		8	7	6	5

Resurvey of the Uintah Indian Reservation Boundary .....Page 2  
 The Survey of the Subdivision of Section 26.....Page 16

TOWNSHIP 2 NORTH, RANGE 1 EAST,  
UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

The following field notes describe the dependent resurvey of a portion of the Uintah Indian Reservation Boundary from Mile Post 36 1/2 to Mile post 38 1/2, a portion of the south boundary and a portion of the subdivisional lines, and the subdivision of section 26, in T. 2 N., R. 1 E., Uintah Special Meridian, Utah.

**History of Surveys****Surveyed by****Retr. or Resurveyed by****UINTAH INDIAN RESERVATION BOUNDARY**

All	C.L. DuBois	1875		
All			A.H. and F.M. Brown	1903
Remonumentation			A. Nelson	1961
Portion			R.A. Zaninovich	1990
Portion			L.V. Judd	1993

**NORTH BOUNDARY**

All	J.H. Martineau	1903		
-----	----------------	------	--	--

**SOUTH BOUNDARY**

Portion	C.L. DuBois	1875		
Portion	J.H. Martineau	1903		
Portion			L.V. Judd	1993

**EAST BOUNDARY**

All	J.H. Martineau	1903		
All			R.A. Zaninovich	1990

**WEST BOUNDARY**

All	J.H. Martineau	1903		
Remonumentation			A. Nelson	1961
Remonumentation			F.D. Reynolds	1968
Portion			L.V. Judd	1993

**SUBDIVISION**

All	J.H. Martineau	1903		
Portion			V. Lane	1957
Remonumentation			A. Nelson	1961
Portion			R.A. Zaninovich	1990
Portion			L.V. Judd	1993

TOWNSHIP 2 NORTH, RANGE 1 EAST,  
UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

The survey was executed in accordance with specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 815, dated April 18, 1994.

The direction of lines were determined by hour angle observations of the sun and Polaris, carried forward by sustained angulation. Distances were determined by electronic measurement.

Preliminary to the resurvey the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the southeast corner of section 36, which will now function as a B.L.M. control station, was determined by GPS observations, is as follows:

Latitude: 40° 31' 12.08" N.      Longitude: 109° 49' 14.95" W.  
N.A.D. 1927

The mean magnetic declination as determined from numerous readings throughout the survey is: 13 1/2° E.

---

Dependent Resurvey of a Portion of the  
Uintah Indian Reservation Boundary,  
T. 2 N., R. 1 E., Uintah Special Meridian, Utah

---

Reestablishment of the Survey Executed by  
C.L. DuBois in 1875, and the Resurvey by  
A.H. and F.M. Brown in 1903

---

Beginning at the 36 1/2 mile post on the Uintah Indian Reservation Boundary, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, marked and witnessed as described in the official record of the remonumentation of certain corners in T. 2 N., R. 1 E. in 1961.

From this mile post, the true point for the closing corner of sections 25 and 26, bears S. 75° 26' E., 19.83 chains distance.

From which the amended monument bears N. 0° 12' E., 0.17 chains distance, monumented with an aluminum post, 2 1/2 inches in diameter, projecting 6 inches above ground, with aluminum cap marked as described in the official record of the 1990 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE  
UINTAH INDIAN RESERVATION BOUNDARY,  
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

N. 79° 06' W., between mile post 36 1/2 and mile post 37, on the Uintah Indian Reservation Boundary.

Over rolling land.

- 21.335 Point for the north 1/4 section corner of section 26, on the Uintah Indian Reservation Boundary, at midpoint between closing corners.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

UIB

1/4 S26

T2N R1E

1994

Corner is located 8 1/2 links east of fence corner, with fences projecting S. 79° E., N. 79° W. and S.

- 41.04 Mile post 37, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, marked and witnessed as described in the official record of the remonumentation of certain corners in T. 2 N., R. 1 E. in 1961.

N. 71° 46' W., between mile post 37 and mile post 38 on the Uintah Indian Reservation Boundary.

- 21.89 The closing corner of sections 26 and 27, monumented with a sandstone 26x12x5 ins., firmly set, projecting 10 ins. above ground, plainly marked 4 grooves on E and 2 grooves on W faces, and CC on S face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

UIB

S27 | S26

CC

T2N R1E

1994

Deposit the marked stone alongside the aluminum post.

Corner is located 3 links S of fence line, which bears S. 71° 46' E. and N. 71° 46' W.

DEPENDENT RESURVEY OF A PORTION OF THE  
 UTAH INDIAN RESERVATION BOUNDARY,  
 T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**  
**40.06**

Mile post 37 1/2, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, marked and witnessed as described in the official record of the remonumentation of certain corners in T. 2 N., R. 1 E. in 1961.

N. 71° 47' W., beginning measurement.

**24.605**

Point for the north 1/4 section corner of section 27, on the Uintah Indian Reservation Boundary, at midpoint between closing corners.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

UIB  
 1/4 S27  
 T2N R1E  
 1994

Corner is located 1 link S. of fence line, which bears S. 71° 47' E. and N. 71° 47' W.

**40.02**

Mile post 38, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above mound of stone, marked and witnessed as described in the official record of the remonumentation of certain corners in T. 2 N., R. 1 E. in 1961.

N. 71° 24' W., between mile post 38 and mile post 38 1/2 on the Uintah Indian Reservation Boundary.

**27.42**

The closing corner of sections 27 and 28, monumented with a sandstone, 16x12x6 ins., loosely set under fence line, plainly marked with 3 grooves on the E and W faces, and CC on S face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

UIB  
 S28 | S27  
 CC  
 T2N R1E  
 1994

Deposit the marked stone alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE  
 UTAH INDIAN RESERVATION BOUNDARY,  
 T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS****39.77**

Corner is located in fence line, and 75 links E of trail road, which bears N and S.

Mile post No. 38 1/2, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, marked and witnessed as described in the official record of the remonumentation of certain corners in T. 2 N., R. 1 E. in 1961.

---

Dependent Resurvey of a Portion of the South Boundary,  
 T. 2 N., R. 1 E., Uintah Special Meridian, Utah

---

Reestablishment of the Survey  
 Executed by J.H. Martineau in 1903

---

From the corner of Townships 1 and 2 North, Ranges 1 and 2 East, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, marked and witnessed as described in the official record of the resurvey of a portion of the east boundary in 1990.

This corner will also function as a B.L.M. control station, hereinbefore described.

N. 39° 36' W., between sections 1 and 36, on the south boundary of the township.

Over rolling land.

**40.34**

The 1/4 section corner of sections 1 and 36, monumented with a sandstone, 18x10x8 ins., firmly set, projecting 8 ins. above ground, plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E  
 1/4 S36  
       S1  
       T1N  
       1994

Deposit the marked stone alongside the aluminum post.

Corner is located on S slope, in thick timber and approximately 4 chains N of power line.

---

N. 88° 57' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS  
38.31

The corner of sections 1, 2, 35, and 36, monumented with a limestone, 15x10x6 ins., firmly set, projecting 8 ins. above ground, plainly marked 1 notch on the E and 5 notches on the W edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, with aluminum cap marked:

T2N R1E	
S35	S36
S2	S1
T1N	
1994	

Deposit the marked stone alongside the aluminum post.

---

S. 89° 42' W., between sections 2 and 35, on the south boundary of the township.

Over rolling land.

41.80

The 1/4 section corner of sections 2 and 35, monumented with a sandstone, 14x14x14 ins., firmly set, projecting 4 ins. above ground, plainly marked 1/4 on the N. face, from which the original bearing trees

A cedar, 12 ins. diam., bears S. 40° E., 49 links distance,  
marked 1/4 S2 BT.

A cedar, 12 ins. diam., bears N. 51° 30' W., 42 links distance,  
marked 1/4 S35 BT.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E	
1/4	S35
	S2
T1N	
1994	

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, north of corner.

---



DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 89° 32' W., beginning new measurement.

39.55

The corner of sections 2, 3, 34, and 35, monumented with a sandstone, 18x12x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 2 notches on the E and 4 notches on the W edges. The original bearing trees have been destroyed by fire.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap marked:

T2N R1E	
S34	S35
S3	S2
T1N	
1994	

Deposit the marked stone alongside the aluminum post.

Corner is located on level mesa top, in burned out forest area, and 75 links S of dirt road, which bears NW and SE.

---

N. 89° 44' W., between sections 3 and 34, on the south boundary of the township.

Over nearly level land.

40.19

The 1/4 section corner of sections 3 and 34, monumented with a sandstone, 16x10x8 ins., firmly set, projecting 8 ins. above ground, plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T2N R1E	
1/4	S34
	S3
T1N	
1994	

Deposit the marked stone alongside the aluminum post.

Corner is located 1 chain E of dirt road, which curves W and curves E.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

N. 89° 21' W., beginning new measurement.

41.03

The corner of sections 3, 4, 33, and 34, monumented with a sandstone 12x12x8 ins., firmly set, projecting 8 ins. above ground, plainly marked 3 grooves on the E and W faces.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T2N R1E	
S33	S34
S4	S3
T1N	
1994	

Deposit the marked stone alongside the aluminum post.

Corner is located in thick timber, near W. edge of small drainage, drains S.

---

S. 87° 37' W., between sections 4 and 33, on the south boundary of the township.

Over rolling land.

38.63

The 1/4 section corner of sections 4 and 33, monumented with a sandstone, 18x10x8 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the N face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E	
1/4	<u>S33</u>
	S4
T1N	
1994	

Deposit the marked stone alongside the aluminum post.

Corner is located near southeast edge of small clearing, 50 links N of trail road, which bears NW and SE.

---

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

39.43

S. 89° 55' W., beginning new measurement.

The corner of sections 4, 5, 32, and 33, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above mound of stone, marked and witnessed as described in the official record of the resurvey of a portion of the south boundary in 1993.

---

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 2 N., R. 1 E., Uintah Special Meridian, Utah

---

Reestablishment of the Survey Executed by J.H. Martineau in 1903

---

From the corner of sections 1, 2, 35, and 36, on the south boundary of the township, hereinbefore described.

N. 1° 08' W., between sections 35 and 36.

Over rolling land.

40.57

The 1/4 section corner of sections 35 and 36, monumented with a limestone, 16x12x6 ins., firmly set, projecting 10 ins. above ground, dimly marked 1/4 on the W face and a scattered mound of stone to the W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E  
1/4  
S35 | S36  
1994

Deposit the marked stone alongside the aluminum post.

Corner is located on W slope, 3 chains W of ridge top.

---

N. 0° 24' E., beginning new measurement.

20.01

Point for the N 1/16 section corner of sections 35 and 36.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

N 1/16  
S35 | S36  
1994

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, west of corner.

Corner is located on NE slope, approximately 4 chains S. of dirt trail road, bears NW and SE.

40.02

The corner of sections 25, 26, 35, and 36, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, marked and witnessed as described in the official record of the resurvey of a portion of the subdivisional lines in 1990.

From the corner of sections 2, 3, 34, and 35, on the south boundary of the township, hereinbefore described.

N. 0° 03' E., between sections 34 and 35.

Over rolling land.

41.11

The 1/4 section corner of sections 34 and 35, monumented with a sandstone, 15x11x9 ins., firmly set, projecting 6 ins. above ground, plainly marked 1/4 on the W face, and mound of stone to the W.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E  
1/4  
S34 | S35  
1994

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, west of corner.

Corner is located on nearly level land, in burned forest area, approximately 4 chains NW of small grove of live timber.

N. 0° 18' E., beginning new measurement.

39.72

The corner of sections 26, 27, 34, and 35, monumented with a sandstone, 20x12x8 ins., firmly set, projecting 10 ins. above ground, plainly marked 1 groove on the S, and 2 grooves on the E faces.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

Bearing trees have been destroyed by fire.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 4 ft. base to top, with aluminum cap marked:

T2N R1E	
S27	S26
S34	S35
1994	

Deposit the marked stone alongside the aluminum post.

Corner is located on W slope, approximately 8 chains E of a drainage, which drains S.

From the corner of sections 25, 26, 35, and 36.

N. 89° 50' W., between sections 26 and 35.

Over rolling land.

**20.14**

Point for the E 1/16 section corner of sections 26 and 35, falls in middle of dirt trail road, bears NW and SE.

Drive a railroad spike flush with surface of the road

from which

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears S. 45° E., 45 1/2 links distance, with aluminum cap marked T2N R1E S35 30 FT RM 1994 and an arrow pointing to the corner.

An aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, for a reference monument, bears S. 45° W., 45 1/2 links distance, with aluminum cap marked T2N R1E S35 30 FT RM 1994 and an arrow pointing to the corner.

**40.28**

The 1/4 section corner of sections 26 and 35, monumented with an unrecorded galvanized post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with galvanized cap marked 1/4. The marked stone is buried alongside the galvanized post. The galvanized post is accepted as a faithful and careful perpetuation of the original corner.

I remark the galvanized cap as follows

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

T2N R1E

S26 1/4

S35

BLM

1994

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, north of corner.

No other improvements were made on this corner point.

Corner is located on NW slope, approximately 8 chains S of dirt road, which bears E and W, and in alignment with N and S fence line projecting N.

N. 89° 38' W., beginning new measurement.

40.28 The corner of sections 26, 27, 34, and 35.

N. 0° 27' E., between sections 26 and 27.

Over rolling land.

40.37 The 1/4 section corner of sections 26 and 27, monumented with a sandstone, 15x10x8 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E

1/4

S27 | S26

1994

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, west of corner.

N. 0° 37' E., beginning new measurement.

5.06 The closing corner of sections 26 and 27, on the Uintah Indian Reservation Boundary, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

From the corner of sections 3, 4, 33, and 34, on the south boundary of the township, hereinbefore described.

N. 0° 10' E., between sections 33 and 34.

Over rolling land.

39.33

The 1/4 section corner of sections 33 and 34, monumented with a sandstone, 18x11x8 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W face, and a mound of stone, W of corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E  
1/4  
S33 | S34  
1994

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, west of corner.

---

N. 0° 03' E., beginning new measurement.

39.85

The corner of sections 27, 28, 33, and 34, monumented with a sandstone, 20x12x8 ins., firmly set, projecting 10 ins. above ground, plainly marked 3 grooves on E and 1 groove on S faces, and a scattered mound of stone to the W of the corner.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E  
S28 | S27  
S33 | S34  
1994

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, west of corner.

Corner is located on NE slope, approximately 1.50 chains W of draw, which drains SE.

---

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

**CHAINS**

From the corner of sections 26, 27, 34, and 35.

S. 88° 48' W., between sections 27 and 34.

Over rolling land.

**40.77**

The 1/4 section corner of sections 27 and 34, monumented with a sandstone, 16x11x8 ins., firmly set, projecting 8 ins. above ground, plainly marked 1/4 on the N face, and a mound of stone N of corner. No remaining evidence of the original bearing trees were recovered.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E  
1/4  $\frac{S27}{S34}$   
1994

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, north of corner.

Corner is located on S slope in burned out area.

S. 89° 46' W., beginning new measurement.

**40.54**

The corner of sections 27, 28, 33, and 34.

N. 0° 14' E., between sections 27 and 28.

Over rolling land.

**40.37**

The 1/4 section corner of sections 27 and 28, monumented with a sandstone, 20x12x6 ins., firmly set, projecting 10 ins. above ground, plainly marked 1/4 on the W face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

## CHAINS

T2N R1E  
1/4  
S28 | S27  
1994

Deposit the marked stone alongside the aluminum post.

Corner is located on gentle S slope, with sparsely scattered, burned trees.

N. 0° 24' E., beginning new measurement.

33.01

The closing corner of sections 27 and 28, on the Uintah Indian Reservation Boundary, hereinbefore described.

From the corner of sections 27, 28, 33, and 34.

S. 89° 48' W., between sections 28 and 33.

Over rolling land.

40.01

The 1/4 section corner of sections 28 and 33, monumented with a sandstone, 20x12x6 ins., firmly set, projecting 12 ins. above ground, plainly marked 1/4 on the N face.

The original bearing trees have been destroyed by fire.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap marked:

T2N R1E  
1/4 S28  
S33  
1994

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, north of corner.

S. 89° 52' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL  
LINES, T. 2 N., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

**CHAINS****38.58**

The corner of sections 28, 29, 32, and 33, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, marked and witnessed as described in the official record of the resurvey of a portion of the subdivisional lines in 1993.

---

The Survey of a Portion of Section 26,  
T. 2 N., R. 1 E., Uintah Special Meridian, Utah

---

From the 1/4 section corner of sections 26 and 35.

N. 0° 22' E., on the N - S center line of section 26.

Over rolling land.

**35.115**

The N 1/4 section corner of section 26 only, hereinbefore described.

---

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**FIELD ASSISTANTS**

---

Name	Capacity
Steven Oatman	Surveying Technician

## CERTIFICATE OF SURVEY

I, *Jerry L. Thomas, Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *18th day of April, 1994*, I have *dependently resurveyed the Uintah Indian Reservation Boundary from Mile Post 36 1/2 to Mile Post 38 1/2, a portion of the south boundary, and a portion of the subdivisional lines and the survey of the subdivision of section 26, in Township 2 North, Range 1 East,*

of the *Uintah Special Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

*Dec. 23, 1998*

Date

*Jerry L. Thomas*

(Cadastral Surveyor)

\_\_\_\_\_

Date

\_\_\_\_\_

(Cadastral Surveyor)

## CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of the Uintah Indian Reservation Boundary from Mile Post 36 1/2 to Mile Post 38 1/2, a portion of the south boundary, and a portion of the subdivisional lines and the survey of the subdivision of section 26, Township 2 North, Range 1 East, Uintah Special Meridian, Utah,*

executed by *Jerry L. Thomas, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved

*Jan. 11, 1999*

Date

*Daniel W. Webb*

(Chief Cadastral Surveyor for Utah)